


- 開箱尺寸
- DIMENSIONS OF ENCLOSURE BOX (L1 & L2)
- | SHUTTER WIDTH | L1 (mm) | L2 (mm) |
|---------------|---------|---------|
| 10            | 1100    | 800     |
| 20            | 1450    | 1200    |
| 30            | 1550    | 1100    |
| 40            | 1750    | 1400    |
- \* AN EVEN FLOOR LEVEL MUST BE PROVIDED THROUGHOUT TRAVEL OF THE SHUTTER 簾頁軌跡所經的地面要在同一水平線上
- ENCLOSURE BOX 開箱
  - STEEL HANGER 穩固件
  - TOP TRACK 導軌
  - RECEIVING CHANNEL 接收槽
  - POLYCARBONATE CURTAIN 雅士牌簾頁
  - PORTABLE BOTTOM TRACK 可移動地軌
  - LEADING EDGE 牽引件
  - FLOOR SOCKET W/ SPRING RETURN 地插連防塵
  - DUST COVER 塵蓋

SHUTTER WIDTH	L1 (mm)	L2 (mm)
10	1100	800
20	1450	1200
30	1550	1100
40	1750	1400



CHUNG TAI  
ROLLER SHUTTERS CO. LTD.  
UNIT 7, G/F, KIN FAT INDUSTRIAL CENTRE,  
KIN FAT ST., TUEN MUN, N.T.  
TEL: +852 2465 9323  
FAX: +852 2456 1364  
E-mail: info@chungtai-rs.com.hk

DRAWING NO.: L-CS

COMPONENTS OF (CLEARSEAL II & CLEARSEAL IIS) POLYCARBONATE CURTAIN MOTOR OPERATED Laterally Sliding Shutter 雅士牌(透視)電動橫趟開組件圖